

# POLYCRACKER® is the only Prep Wash you will ever need.

Instruction for Prep Washing, Final Prep Wash  
and Poly-Silicone Removal

REMOVES ARMOR-ALL AND MOLD RELEASE

**For Best Results, Apply to Area Before  
Starting Work and Before Painting**

Follow these simple steps:

1. Prepare mixture consisting of 50% POLYCRACKER solution and 50% water. First, add POLYCRACKER to fill line on bottle. Then fill remainder of bottle with water.
2. Shake well.
3. Apply a misting spray directly onto the dry surface or apply after pouring on clean, dry cloth. Brush into hinge, lock and similar hard to reach places.
4. Let stand 2 to 4 minutes - make sure surface stays damp.
5. Wipe surface with a clean dampened cloth (use water only)
6. Wipe surface a second time with a clean dry cloth.
7. Surface is now ready to prime or paint.

For best results, apply POLYCRACKER again before painting, after repairs have been made.  
**NOTE:** POLYCRACKER is to be used for the removal of poly-silicone.

**POLYCRACKER DOES NOT REMOVE HARDENED TAR.**

Do not use on hot metal or in sunlight- POLYCRACKER will evaporate and not have time to work.

Sometimes it is difficult to tell if a car has a polymer-silicone finish or not. Do not take chances.

Use POLYCRACKER on all your repair and paint jobs.

When used as directed, POLYCRACKER is the most economical prep wash you can buy. You can count on it every time to give you a worry-free surface for all your paint jobs.

**FOR BLENDING/SPOT REPAIRS:** When all repairs are completed, wipe POLYCRACKER across the panel (old finish) and beyond the area to be painted and rinse again. Sanding on the panel is not necessary for adhesion of the new finish and blend.

Before applying any primer or finish, be sure that all moisture has evaporated from the panel. Radiant heat may be used to facilitate drying. Immediately apply primer or finish coat(s). Do not delay more than 30 minutes before applying the first coat of the new finish. You may pick up contaminants from air if you wait longer.

## **POLYCRACKER®**, INC.

487 DIVISION STREET  
BOONTON, NEW JERSEY 07005  
(973) 335-2828 / FAX: (973) 402-7222

[polycracker@netscape.com](mailto:polycracker@netscape.com)

**CAUTION: MUST BE DILUTED. DO NOT USE POLYCRACKER ON FRESH PAINT. RINSE WITH WATER FROM GLASS SURFACE. HARMFUL IF SWALLOWED. IF CONCENTRATE GETS INTO EYES, RINSE THOROUGHLY WITH WATER.**